

UTILITY DUCT

LOADING CHART

PRODUCT TYPE	SIZE	LENGTH	PCS/LIFT	FT/LIFT	LIFTS/LOAD	% LOAD	FT/LOAD
EB/DB DUCT 20' LENGTH	1	20	400	8,000	20	5.00%	160,000
	1 1/2	20	225	4,500	20	5.00%	90,000
	2	20	140	2,800	20	5.00%	56,000
	2 1/2	20	131	2,620	16	6.25%	41,920
	3	20	100	2,000	12	8.33%	24,000
	3 (West)*	20	100	2,000	16	6.25%	32,000
	3 1/2	20	63	1,260	16	6.25%	20,160
	4	20	57	1,140	12	8.33%	13,680
	4 (West)*	20	57	1,140	16	6.25%	18,240
	5	20	38	760	12	8.33%	9,120
	5 (West)*	20	38	760	16	6.25%	12,160
	6	20	26	520	12	8.33%	6,240
6 (West)*	20	26	520	16	6.25%	8,320	
CSA DB2 10' LENGTH	2	10	234	2,340	32	3.13%	74,880
	3	10	100	1,000	32	3.13%	32,000
	4	10	63	630	32	3.13%	20,160
CSA DB2 20' LENGTH	2	20	234	4,680	16	6.25%	74,880
	3	20	100	2,000	16	6.25%	32,000
	4	20	63	1,260	16	6.25%	20,160
TYPE C DUCT	4	20	63	1,260	16	6.25%	20,160

Lifts/Load based on unit size—Do not Exceed Maximum Weight per Truckload: 45,000 lbs.

(West)*: Includes JM Eagle plants in Tacoma, WA; Sunnyside, WA; McNary, OR; Cameron Park, CA; Stockton, CA; Perris, CA; Fontana, CA; Visalia, CA.

 PKG SPEC REQUIRES REVISION