

WELL CASING

SUBMITTAL AND DATA SHEET

*ANSI/NSF 61-14

	NOMINAL PIPE (IN)	AVERAGE O.D. (IN)	APPROX. I.D. (IN)	MIN. T. (IN)	APPROX. WEIGHT (LBS/100')
SDR 32.5	4	4.500	4.20	0.138	130
	5	5.563	5.179	0.171	192
	6	6.625	6.18	0.204	270
	8	8.625	8.05	0.265	460
SDR 26	4	4.500	4.13	0.173	160
	4 1/2	4.950	4.54	0.190	190
	5	5.563	5.10	0.214	240
	6	6.625	6.07	0.255	330
	8	8.625	7.91	0.332	590
	10	10.750	9.86	0.413	910
SDR 21	12	12.750	11.70	0.490	1280
	4	4.500	4.04	0.214	190
	4 1/2	4.950	4.44	0.236	240
	5	5.563	4.99	0.265	300
	6	6.625	5.94	0.316	410
	8	8.625	7.74	0.410	690
	10	10.750	9.65	0.511	1110
SDR 17	12	12.750	11.45	0.606	1570
	4	4.500	3.906	0.265	234
	4 1/2	4.950	4.32	0.291	290
	5	5.563	4.86	0.327	360
Schedule 40	6	6.625	5.79	0.390	520
	2	2.375	2.027	0.154	71
	4	4.500	3.99	0.237	210
	4 1/2	4.950	4.41	0.248	250
	5	5.563	5.01	0.258	290
	6	6.625	6.02	0.280	370
	8	8.625	7.93	0.322	590
	10	10.750	9.96	0.365	780
	12	12.750	11.88	0.406	1030

* Prior to ordering or specifying, please consult JM Eagle™ for product and/or listing availability.

Product Standard: ASTM F480*
 Pipe Compound: ASTM D1784 Cells Class 12454
 Certifications: ANSI/NSF Standard 61
 End Finish: Belled End
 Pipe Length: 20 feet laying length
 Installation: JM Eagle™ Installation Guide

*Manufacturing dimensions and testing will meet pipe Stiffness, Flattening, Impact and Tup Puncture in accordance to specification ASTM F480.